

MATERIAL SAFETY DATE SHEET

Date: 23.02.2019

	I – IDE	INTIFICATION OF THE PRODUCT	AND COMPANY			
Trade Name		Active engine flush RESURS; Clever engine flush RESURS; Rapid engine flush RESURS (Concentrate), Rapid engine flush RESURS, Engine Flush iMagnet				
Purpose		For flushing of petrol and diesel oil systems				
Producer		VMPAUTO LLC				
Address		Promyshlennaya str. 40A, 198099, Saint-Petersburg, Russia				
Tel/Fax: E-mail		+7 (812) 601-05-50 / 601-05 59, ex	xport@vmpauto.com			
		II – HAZARDS IDENTIFICAT				
Classification		The material is not hazardous as defined in TC 2384-025-45540231-2006.				
Hazard for health		It is not hazardous for health under normal application conditions.				
Ecological hazard		It is not classified as hazardous su	bstance for environm	ient.		
		III - COMPOSITION				
Chemical composition		The composition consists of mineral oil, liquid paraffins, anticorrosive, anti				
Name of the own boot	01	frictional and washing-dispergated		040	MDO	
Name of the product	Chemic	al name	Volume %	CAS- Number,m g/m ³	MPC, w.a.	
Liquids for washing the engine	Mineral Oil "I40"		30-58	8042-47-5	4,0	
	Glycol ether		Up to 3%	74869-22-0	10,0	
	Liquid paraffins		12 - 17	35884-42-5	300,0	
	Neonol "AΦ 9-6"		5-7	8020-83-5	Not regulated	
		IV - FIRST-AID MEASUR	ES			
General information		It is not hazardous for health unde	r normal application of	conditions		
Eyes		It is not hazardous for health under normal application conditions. Washout eyes with big quantity of water during 15 minutes. If irritation continues, consult a doctor.				
Skin		Take off dirty dress. Polluted skin washout with soap. Under normal use doctor's consultation is not necessary.				
Anatomical airways		Go outside. If breathing is difficult – consult a doctor.				
Digestive system		Do not induce vomiting. If health is worth, consult a doctor.				
V- ME	ASURES AN	ID MEANS OF PREVENTING FIRE	AND EXPLOSION I	HAZARD		
Firefighting tools		Firefighting tools are used that don't keep on fire (sand, large felt melt, water, chemical foam, dry powder etc.)				
Special hazard		Risk is not identified.				
Prohibited means		Do not use water in the form of a jet.				
Means of individual protection		Protective suit, respirator, isolated gas mask.				



MATERIAL SAFETY DATE SHEET

Poured product is swamped doesn't let product get in drink	with sand, clay	ring and Liquidation of accidents and emergences of or other inertial material is scooped up mechanically. Utilize proper way. It water pools surfaces, sewerage and soil.			
doesn't let product get in drink VII- STORAGE REGUL	ing sources on				
VII- STORAGE REGUL	ing sources on	water pools surfaces, sewerage and soil.			
	ATIONS OF C	3			
General safety rules		CHEMICAL PRODUCTION AND ITS TREATMENT UNDER HANDLING			
General safety rules		OPERATIONS			
	Under normal use of RESURS product is stable and does not require special protective equipment. Product RESURS relates to hardly combustible and low toxic				
Handling	class				
Handling Storage		It is not necessary under normal use. Use rubber gloves.			
Recommended materials		It is not necessary under normal use.			
		It is not necessary under normal use. It is not necessary under normal use.			
Incompatible materials		FOR HAZARDS AND MEANS OF INDIVIDUAL PROTECTION			
		er normal use of RESURS preparation, product is stable and it doesn't require			
General information	spec	special protective equipment. Preparation of RESURS is related to hard-combustible and low-toxic products.			
Protection of breathing	It is not required under right application.				
Protection of eyes	It is r	It is not required under right application.			
Protection of skin	It is r	It is not required under right application.			
Protection of hands	Use rubber gloves.				
	IX – PH	HISICAL AND CHEMICAL PROPERTIES			
Physical condition		Viscous liquid of yellow color.			
Temperature of flash-point		80 °C – for product "Adaptive engine flush RESURS",			
		210 °C – for product "Clever engine flush RESURS".			
Density, g/cm ³ , not less then		0,850			
Funnel viscosity according to device "AK-1M", u.		40-60			
Corrosion tests		Withstand			
	X – S	TABILITY AND REACTION CAPACITY			
Chemical stability		Material is stable under normal use conditions and storage.			
Hazard of polymerization		Not hazardous			
Incompatibility		With strong oxidants			
Hazardous products of decom	position	Under normal storage conditions, formation of hazardous products is not supposed.			
	ΧI	-TOXICOLOGICAL INFORMATION			
Product is not hazardous for GOST 12.1.1.007).	organism and	relates to IV Class of Hazard (substances are moderately hazardous as in			
Irritation of skin		Slight irritation			
Irritation of eyes		Slight irritation			
Other toxicological information		Information is based on properties of raw materials. It is not proved its carcinogenic or mutagenic property.			
	Х	II – ECOLOGICAL INFORMATIOM			
Eco-toxicological data were not The information above is ba products.		cially for this product. edge of components and results of eco-toxicological research of analogue			
Acute toxicology	Product is con	uct is considered non-toxic. Mineral oil does not make chronic action on water organisms			
under concent pools.		ration less than 1mg/l. It has slow toxic effect on fish and micro flora of water			
		ir in the presence of other substances does not form toxic compounds.			



MATERIAL SAFETY DATE SHEET

Movement	Product is not mixed with water. Under penetration in soil it is absorbed with its particles.
Stability	Product is not fast bio-degradable. Basic components are bio-degradable, but product has non bio-degradable substances.
Bio-accumulation	Some components can accumulate in alive organisms.
Other impacts	It is not supposed a possibility of destruction of ozone layer and influence on global warming.
Protection of environm wastes are absent.	ent is provided under production with hermetically sealed technical equipment. Liquid and solid

XIII - RECOMMENDATIONS FOR WASTE UTILISATION (REMAIDERS)

Wastes (remainders) place in strictly labeled container for next utilization and regeneration. Any means of actions with wastes must be appropriate to all local and public laws and normative acts.

Properties of transportation It is not classified as a hazardous load. UN number

N/A Hazard class N/A

It is not subjected to norm ADR/RID ADR/RID (Road transport)

It is not subjected to technical conditions IMDG **IMDG** (Sea transport)

IATA (Air transport) It is not subjected to norms of "IATA Dangerous Goods Regulation (DGR)"

edition 60th, 2019

Product can be transported with any transport.

XV - NATIONAL AND INTERNATIONAL LAGISLATION

Laws of Russian Federation:

"About technical regulation";

"About environmental safety":

"About sanitary-epidemiological well-being of the population".

Under the international conventions and agreements it is not subjected.

XVI - ADDITIONAL INFORMATION

Contents and form of the given document corresponds to requirements:

- 1. GOST 30333-2007 "Passport of safety of chemical production. General requirements".
- 2. GOST 12.1.007-76 « Harmful substances. Classification and general safety requirements".
- 3. GOST 12.1.005-88 «General sanitary-epidemiological requirements to air of working zone".
- 4. GN 2.1.5.1315-03 "Maximum permissible concentration of (MPC) of chemical substances in water of water pools for household-drinking and cultural-household water management".
- 5. FOCT 19433-88 «Hazardous loads. Classification and labeling".

Information in this Safety Card corresponds to the latest modern level of our knowledge about product.

Product is applied and used in accordance to given advises. Information in this Safety Card does not compile instruction on the workplace.

Data contains in the given document have to be opened to any potential users of this product.

Utilization recommendations:

This product is applied and used as compound for sealing of threaded connections as specified in instruction on package for sealing of threaded connections.

Data: Abbreviation: N/A = was not identified;

N/D = is not determined.

For getting additional information about product, contact Sales Department of VMPAUTO

(Tel/Fax: +7 (812) 601 05 50.

